

<u>Truck Figure 8 & Enduro & Drag Races</u> 2025 Official Rules

Eligible Trucks: 1976 and up. No larger than ½ TON. Trucks up to ½ TON 4x4 MUST remove front drive shaft. NO OTHER 4X4 trucks permitted EVEN with 4x4 disabled. Any cab, only standard truck beds (No flat or custom beds). All components of the truck must remain Stock. No lift kits or over size tires.

- 1. All glass except the windshield must be removed. Cracks allowed if the driver has a clear view. The window area behind the driver's head must have a clear piece of Lexan or netting placed in this area, for driver's safety, if cab is extended this is not needed.
- 2. All Rugs, headliners, door panels or any other items that can burn must be removed except the dash and seat. The interior needs to be clean with no glass or loose objects.
- 3. Doors MUST be welded or chained shut. Min. 5/16 chain. No ropes or straps.
- 4. Hoods must be secured shut. If the hood opens during the race truck will be black flagged. 5-inch hole must be placed in Hood to spray fire extinguisher into engine compartment for fires.
- 5. DRIVERS MUST USE FULL FACE HELMETS WITH EYE PROCTION. NO SHORTS, DRIVER MUST WEAR FULL PANTS AND SHIRT.
- 6. Seat may be replaced with another.
- 7. OEM seat belts must be used, or a racing seat belt is highly recommended.
- 8. ALL mirrors and plastic trim on the outside of the truck need to be removed. No Glass in Doors!
- 9. Inner roll cage permitted. No bars outside of truck Allowed.
- 10. Air bags must be removed if equipped. Disconnect impact sensors.
- 11. Battery must remain in stock location.
- 12. Exhaust may be cut, must travel past driver under truck, NO exhaust may exit from side of truck, in driver's compartment or up behind driver from truck's bed. Exhaust may exit straight up from hood, Minimum of 6 inches high from hood line. **No Turbo's or Super chargers.**
- 13 Fuel tanks must stay in stock location between frame rails only. Reposition of fuel tank not permitted.
- 14. Bumpers must be intact and safely attached. Prefer stock but steel aftermarket ok, like stock. No wood or other material.
- 15. Two (2) chains required at each end of bumpers wrapped around and connected to frame tightly, this is to prevent the bumper from coming off if damaged and is Mandatory
- 16. Suspension CAN NOT be lifted or jacked up. Ride height must remain stock.
- 17. No Anti-Freeze. Water Only!
- 18. Tires not ALLOWED bias ply racing tires, re-caps, or studded. Tires MUST HAVE M&S SYMBOL (Mud & Snow) shown on the sidewall or TREADWEAR rating NO LESS than 250. No over sized tires to trucks stock appearance. ALL wheel weights must be removed.

EVENT RULES: All drivers must always follow the direction of Track personnel. Drivers must be alerted to track flags and lights and obey them immediately. Drivers must avoid making contact with other drivers aggressively with intent to spin them out. If a driver is seen continually disobeying this rule, they will be black flagged from all events.

ALL DRIVERS MUST ATTEND SCHEDULED DRIVERS MEETING

The rules and/or regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events, these rules shall govern the condition of all Seekonk Speedway events and by participating in these events, and all participants are deemed to have complied with these rules.

No express or implied warranty of safety shall result from publication of, or compliance with these rules and/or regulations, they are intended as a guide for the conduct of the sport and are in no way a guarantee against injury, or death to participants, spectators, or others.